

```
usr@ROLTEK:/#  
usr@ROLTEK:/#  
usr@ROLTEK:/#  
usr@ROLTEK:/# vi /etc/config/wireless  
usr@ROLTEK:/#  
usr@ROLTEK:/# █
```

```
option country 'CN'  
option country_web 'CN'  
option htmode 'auto'  
option dbdc_enable '1'  
  
config wifi-iface 'wlan0'  
option device 'wifi0'  
option network 'lan'  
option mode 'ap'  
option ssid 'USR-test'  
option key '12345678'  
option encryption 'mixed-psk'  
option ifname 'ath0'  
option disablecoext '1'  
  
config wifi-iface 'sta0'  
option device 'wifi0'  
option network 'wwan0'  
option mode 'sta'  
option ifname 'ath3'  
option extap '1'  
option vap_ind '1'  
option wds '0'  
option disabled '0'  
I /etc/config/wireless [Modified] 17/88 19%
```

```
usr@ROLTEK:/#  
usr@ROLTEK:/#  
usr@ROLTEK:/#  
usr@ROLTEK:/# vi /etc/config/wireless  
usr@ROLTEK:/#  
usr@ROLTEK:/#  
usr@ROLTEK:/# uci commit wireless  
usr@ROLTEK:/#  
usr@ROLTEK:/#  
usr@ROLTEK:/# reboot  
usr@ROLTEK:/# █
```

Waiting the router to reboot.....and check the information on web page, it has changed as hoped.

2.4G AP1

2.4G AP2

5.8G AP1

5.8G AP2

MAC-Filter

Client Information

Status

Mode: Master

SSID: USR-test

BSSID: D4:AD:20:D1:81:DF

Channel: 6 (2.437 GHz)

Tx-Power: 20 dBm

Enable

☒

Hide SSID

☐

SSID

USR-test


Encryption

mixed-psk

▼

Key


12345678



HW Mode

11axg

▼

 If STA is enabled, the configuration is affected by STA.