

USR-ISF005P Specification



USR-ISF005P

5-port 10/100BASE-TX Industrial PoE Switch

Industrial PoE switch, 4 Port 10/100Mbps PoE ports + 1 port ethernet uplink , for connecting with devices like computer, switch, hub, server, etc, as well as powering network camera, industrial VoIP phone, wireless AP and other PoE supported devices. Specially designed for harsh outdoor applications. Its 6KV network port surge protection can adapt to harsh outdoor environment and ensure the reliability of the uninterrupted PoE system. Power input also chooses industry-standard types of power.

Interface

- 5-port 10/100Base-Tx RJ-45 with auto negotiation and auto-MDI/MDI-X function
- 4-Port PoE, 802.3at/af support, 30W max. each port

Industrial conformance


- 48V to 57V DC, redundant power input
- -40°C to 85°C operating temperature
- IP40 aluminum housing
- Supports 6KV DC Ethernet ESD protection
- Supports 6KV DC EFT protection for power line
- Free Fall, Shock and Vibration Stability
- DIN-rail and wall-mountable hardware design

Specifications:

Model No.	USR-ISF005P
10/100BASE-TX Port	5 port RJ-45 auto-MDI / MDI-X
PoE Specification	PoE Standard: IEEE802.3af/ IEEE802.3at
	PoE ports:1-4 port support PoE
	Power Output: Max. 15.4 watts (IEEE 802.3af) Max. 30 watts (IEEE 802.3at)
	PoE port Auto detect AF/AT devices
	Output Voltage: DC48V
	Power Pin Assignment:1/2+;3/6-
	Power Type: End-span(Mid-span optional)
Performance Specification	Bandwidth: 1.6Gbps Packet Buffer Memory:1Mbit Packet Forwarding Rate:1.2Mpps MAC Address Table: 2K
Installation	DIN rail
Maximum Frame Size	9000bytes packet size
Flow Control	Back pressure for half duplex, IEEE 802.3x pause frame for full duplex
Enclosure	IP40 aluminum housing
LED Indicator	Power: Red Ethernet: Yellow POE: Green
Power Input	48 to 57V DC
Surge protection	±4KV
Network Protocols	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u;100Base-TX/FX;

	IEEE802.3ab 1000Base-T; IEEE802.3z 1000Base-X; IEEE802.3x;
Network cables	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤10meter) 1000BASE-TX: Cat6 or later UTP(≤100 meter)
Industry Standard	FCC CFR47 Part 15,EN55022/CISPR22, Class A IEC61000-4-2 (ESD): ±8kV (contact), ±12kV (air) IEC61000-4-3 (RS): 10V/m (80~1000MHz) IEC61000-4-4 (EFT): Power Port: ±2kV; Data Port: ±1kV IEC61000-4-5 (Surge): Power Port: ±1kV/DM, ±2kV/CM; Data Port: ±1kV IEC61000-4-6 (CS): 3V (10kHz-150kHz); 10V (150kHz-80MHz) IEC61000-4-16 (Common mode conduction): 30V (cont.), 300V (1s)
Certification	CE FCC Rohs compliance
MTBF	>300,000hours
Dimensions (W x D x H)	118 x 85.7 x 33.5 mm
Weight	Product Weight: 0.36KG Packing Weight: 0.46KG
Working Environment	Working temperature: -40~85℃ ; Storage temperature: -40~85℃ Relative Humidity: 5%~95 %(no condensation)

Dimensions



Ordering Information

USR-ISF005P	4-Port RJ45(PoE) +1Port RJ-45 uplink Industrial PoE Switch,100Mbps
--------------------	--